


Screen Pixel pitch(mm)	5mm
<p style="text-align: center;">Module</p> 	<ul style="list-style-type: none"> <li>• Pixel pitch: 5mm</li> <li>• Density:40000 Pixels Per Square Meter</li> <li>• Lamp origin: R/G/B Nationstar SMD2727</li> <li>• Module Size: 320mm W × 160mm H</li> <li>• Module resolution: 64 Pixel Wide × 32 Pixels Height</li> <li>• Cabinet size: 640mm x 640mm</li> <li>• Cabinet Pixel Size 128 x 128 pixels</li> <li>• Best viewing distance: 6~100m</li> <li>• Best viewing angle: H 140°, V 140°</li> <li>• Environment temperature: -22°F ~ +194°F</li> <li>• Working temperature: -5°F ~ +122°F</li> <li>• Module weight: About 1.2 LB</li> <li>• Cabinet Weight: 28 lb</li> <li>• OEM Ethercon / Powercon Weather proof connectors</li> </ul>
Power	<ul style="list-style-type: none"> <li>• Working voltage: AC ~60HZ, 110V – 220V ±15%</li> <li>• Most power consumption: 24000W Per Square Meter</li> </ul>
Control system	<ul style="list-style-type: none"> <li>• Operating system: WIN XP/ windows 7, 8, 10</li> <li>• Control mode: Wired / Wireless network / USB</li> <li>• Scalable / Non Scalable options available for processors</li> </ul>
Main Parameters	<ul style="list-style-type: none"> <li>• Driving IC: MBI5124 Led Driver</li> <li>• Scan mode: 1/8</li> <li>• Refresh rate: ≥1920 Hz/s</li> <li>• Grey scale 4096 levels / 16.7 million Color processing</li> <li>• Full white brightness: ≥6500cd/m2</li> <li>• Brightness adjustment mode: 255 levels available</li> <li>• Life-span: 100,000 hours</li> <li>• Protection Front / Back: IP43 / IP54</li> </ul>



**MODLE: RDL- OR5**

[www.RedDotLogics.com](http://www.RedDotLogics.com)